



# LouieP Séries

## P-M10TR Steam Sterilizer



Your Reliable Sterilizer Partner in Dental Clinics and Healthcare Centers



*“In the field of observation, chance favors only the prepared mind.”*

— Louis Pasteur, the 19th century  
Scientist, Microbiologist

The LouieP Séries is the first steam sterilizer added to the AG Neovo Healthcare Dental product lines to fit the rising need for sterile products for patient care, particularly in dental offices and healthcare centers/organizations. It is named in honor of Louis Pasteur, the pioneer in the procedures of disinfection and sterilization in the 19th century, as paying our tribute to the greatest scientist.

LouieP Séries P-M10TR is an ideal alternative steam sterilizer for the dental clinics and healthcare centers. Featuring dynamic air-removal technology, pre-programmed cycle and closed-door drying, it allows high-efficiency operation to sterilize wrapped instruments with less system errors. Built with ASME certified pressure chamber and auto-disconnect safety mechanism, it provides a safe and sterile environment for your daily operation.

## Key Features

### Safety

- 2-Step door opening protection
- Closed-door drying design
- Over pressure and temperature control with auto-disconnect mechanism

### Reliability

- FDA cleared
- ASME certified pressure chamber



### Performance

- Dynamic Air-removal Technology
- Post-vacuum drying for extra dryness


### Efficiency

- Automatic water filling
- Simple press operation
- Easy USB data logging for sterilization cycle report


## Specifications

Model	P-M10TR
Chamber Size	10.2" (26 cm) Diameter x 17.7" (45 cm) Depth
Overall Dimensions (W x H x D)	21" x 17.4" x 25.8" (53.3 cm x 44.2 cm x 65.5 cm)
Minimum Countertop Area (W x D)	29" x 29.8" (73.7 cm x 75.7 cm)
Volume	6.3 Gal (24 liters)
Tray (W x D)	Three (6.25" x 15" / 15.9 cm x 38.1 cm)
Voltage / Power (heater)	12A / 120VAC 60Hz / 1400W
Programmed Cycle	270°F Unwrapped, 270°F Wrapped (Pouches), 250°F Wrapped (Packs), Handpieces, B.D. Test (Cleaning), Pump Test, Re-Dry
Water Reservoir Capacity & Filling Access	1.1 Gal (4.2 liters) & Top (Rear)
Closed Door Drying	Yes
Data Logger	Yes (via USB port)
Unit Weight	127.9 lbs (58 kg)
Shipping Weight	134.5 lbs (61 kg)
Safety Standards	IEC 61010-1, 3rd Edition IEC 61010-2-040:2015  ASME Boiler & Pressure Vessel Code, Section VIII, Division 1
Certifications	ANSI/AAMI ST55:2016
Warranty	2 year limited


## Accessories



Tray Frame with  
3 Stainless Steel  
Trays



Tray Holder



Heater Cover



Cleanser for Chamber



USB Flash Drive  
(incl. data reader  
software)

Note: Product specifications and accessories may vary and be subject to change without prior notice.

Please contact a sales representative for more details.

2362 Qume Drive, Suite A, San Jose, CA 95131, U.S.A.

Tel: 1-408-321-8210 / Fax: 1-408-321-8211

e-mail: [sales.usdental@agneovo.com](mailto:sales.usdental@agneovo.com)

[healthcare.agneovo.com](http://healthcare.agneovo.com)

© 2020 AG Neovo. All rights reserved. The name AG Neovo is a trademark of AIC. All trademarks and company names are the property of their respective owners.